

## JXSC Mine Machinery Factory Symons Cone Crusher Specification

| Model      | Cavity Type   | Stroke<br>(mm) | Max.Feeding<br>Size<br>(mm) | Discharging<br>Opening<br>Adjusted<br>Scope(mm) | Capacity(t/h) | Motor<br>Power(kw) | Weight(t) |
|------------|---------------|----------------|-----------------------------|-------------------------------------------------|---------------|--------------------|-----------|
| DN1650C2-D | Coarse        | 34             | 300                         | 35-65                                           | 280-610       | 250                | 35        |
| DN1650C-D  | Coarse        | 34             | 260                         | 30-60                                           | 2665-580      | 250                | 35        |
| DN1650Z-D  | Medium Coarse | 34             | 240                         | 25-60                                           | 240-550       | 250                | 35        |
| DN1650S-X  | Fine          | 28             | 130                         | 20-45                                           | 180-350       | 250                | 35        |
| DN1400C-D  | Coarse        | 30             | 235                         | 30-60                                           | 210-530       | 220                | 25        |
| DN1400Z-D  | Medium Coarse | 30             | 215                         | 25-50                                           | 200-500       | 220                | 25        |
| DN1400Z-X  | Medium Coarse | 25             | 180                         | 22-45                                           | 180-475       | 220                | 25        |
| DN1400S-X  | Fine          | 25             | 100                         | 19-40                                           | 130-260       | 220                | 25        |
| DN1200C-D  | Coarse        | 22             | 180                         | 19-50                                           | 110-250       | 132                | 16        |
| DN1200S-X  | fine          | 15             | 80                          | 16-40                                           | 80-180        | 132                | 16        |
| DN1000C-D  | Coarse        | 20             | 160                         | 16-35                                           | 70-215        | 110                | 14        |
| DN1000Z-D  | Medium Coarse | 18             | 115                         | 16-30                                           | 55-135        | 110                | 14        |
| DN1000S-X  | fine          | 15             | 80                          | 10-25                                           | 47-90         | 110                | 14        |

Address: Ganzhou, China

Mobile Phone/WhatsApp:  
+86-13879771862  
Email:sales@jxscmachine.com  
www.mineraldressing.com

